



# 1000



## SEMI-PERMANENT RESILIENT FLOOR & CONCRETE SEALER

A diamond-tough floor sealer designed to quickly fill tiny crevices and seal resilient tile and concrete floors making a smooth, durable surface for improved dust control, floor finish adhesion and gloss. This semi-permanent sealer is designed to stay on the floor during normal stripping and degreasing applications; however, it can be removed using a special stripper concentration. Features **stain resistance** to protect tile surfaces from spill of inks, **iodine**, and other materials. Features high initial gloss levels and exceeds industry standards for slip resistance.

### FORMULA FEATURES

- ▶ Stain Resistance (iodine)
- ▶ Optima Enhancer System
- ▶ Diamond-Tough Durability
- ▶ Exceeds Industry Standard for Slip Resistance
- ▶ Semi-permanent Performance
- ▶ Reduces Concrete Dusting

### APPLICATIONS \*READY TO USE

- ▶ Covers 1500-2500 sq. ft. per gallon
- ▶ For use on resilient tile, finished concrete, and terrazzo floors to seal pores and create a durable smooth surface.

### AREAS OF UTILIZATION

- ▶ Schools
- ▶ Office Buildings
- ▶ Grocery Stores
- ▶ Manufacturing Facilities
- ▶ Hospitals
- ▶ Universities
- ▶ Department Stores
- ▶ Hotels
- ▶ Nursing Homes
- ▶ Institutions
- ▶ Restaurants
- ▶ Warehouses

### OTHER FINE FLOOR FINISH/REJUVENATOR FORMULAS

- ▶ HUSKY 1001 Versatile Floor Sealer
- ▶ HUSKY 1018 High Gloss Economy Floor Finish
- ▶ HUSKY 1020 High Gloss Premium Floor Finish
- ▶ HUSKY 1023 Universal Floor Finish
- ▶ HUSKY 1025 High Performance UHS Premium Floor Finish
- ▶ HUSKY 1030 High Solids Premium Floor Finish
- ▶ HUSKY 1041 Multi Purpose Rejuvenator

### OTHER LIQUID/AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Skin Care
- ▶ Odor Control
- ▶ Health Care
- ▶ Industrial Care
- ▶ Carpet Care
- ▶ Specialty Products

# 1000 SEMI-PERMANENT RESILIENT FLOOR & CONCRETE SEALER

## DIRECTIONS

## PRODUCT DATA



1. Before applying sealer, make sure that the floor surface is properly prepared. If the floor has been stripped, all residual stripper should be removed and the pH of the floor should be returned to neutral (6.5-7.5).



2. Always apply thin coats using a clean mop, sprayer, roller, or lamb's wool applicator. It is important to pass the application in a figure 8 pattern to ensure that all areas are thoroughly covered.




3. Allow sealer to dry sufficiently before walking on it or applying additional coats. For standard conditions, allow at least 30 minutes. For thorough drying in poor ventilation areas, dry times will be extended.

4. Repeat steps two and three for additional coats.

Acrylic Polymer Base  
Optical Brighteners  
Metal Interlock  
Repairs Easily  
Removable  
Slip Resistant  
Scuff Resistant  
Superior Adhesion  
Superior Color  
DOT Regulated  
Non Volatile Solids=17%

YES	NO
X	
X	
	X
X	
X	
X	
X	
X	
X	
X	X



### SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#s	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
*Dibutyl phthalate	84-74-2	5mg/M <sup>3</sup>	5mg/M <sup>3</sup>	N/A	1-3
*Ethylene Glycol	107-21-1	50 ppm (c)	50 ppm (c)	N/A	1-3
*Glycol ether DB	112-34-5	N/A	N/A	N/A	1-3
Acrylate Polymer	N/A	N/A	N/A	N/A	10-15

\* This chemical is subject to the reporting requirements for section 313 of title III of the superfund amendments and reauthorization act of 1986 and 40 CFR part 372.

### SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	~212° F	Specific Gravity (H <sub>2</sub> O=1)	1.020
Vapor Pressure (mm Hg.)	N/E	Percent Volatile By Weight (%)	85%
pH (conc.)	8.0	Evaporation Rate (H <sub>2</sub> O=1)	≈1
Solubility in Water	Complete		
Appearance and Odor	White Liquid/Mild Fragrance		

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None Flammable Limits: LEL: N/A UEL: N/A  
Extinguishing Media: Water, CO<sub>2</sub>, Foam or media suitable for surrounding fire  
Special Fire Fighting Procedures: Standard fire fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus.  
Unusual Fire and Explosion Hazards: None Known

### SECTION V - PHYSICAL HAZARDS

Stability  Unstable Conditions to Avoid: None Known  
 Stable

Incompatibility (Materials to Avoid): Do not mix with other chemicals.

Hazardous Decomposition Products or By-products: Thermal decomposition or burning may produce toxic vapors or gases.

Hazardous  May Occur Conditions to Avoid: None Known

Polymerization  Will Not Occur

N/A (Not applicable / Not available)

N/E (Not Established)

8-07

### SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? Skin? X Ingestion? X

Health Hazards (1. Acute and 2. Chronic) 1. Acute: Harmful if swallowed. Eye irritant.

2. Chronic: None Known

Chemical Listed as Carcinogen or Potential Carcinogen:

National Toxicology Program:	<input checked="" type="checkbox"/> No
I.A.R.C. Monographs:	<input checked="" type="checkbox"/> No
OSHA:	<input checked="" type="checkbox"/> No

Signs and Symptoms of Exposure: Irritation or burning sensation.

Medical Conditions Generally Aggravated by Exposure: May aggravate skin disorders or respiratory ailments. Emergency and First Aid Procedures: Eye Contact: Flush immediately with water for 15 minutes. Get medical attention. Skin Contact: Flush with water for 15 minutes. Remove and wash contaminated clothing. Ingestion: Rinse mouth with water. Then drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.

Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.

Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

### SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not expected to be necessary under normal conditions of use. Where exposure cannot be adequately controlled by general or local ventilation, use appropriate respiratory protection to prevent over exposure. An approved dust/mist respirator would be recommended. Ventilation: Local Exhaust: As Necessary Mechanical (General): Adequate Special: N/A Other: N/A Protection Gloves: Water Impervious (Latex, Neoprene) Eye Protection: Chemical Resistant Goggles Other Protective Clothing Or Equipment: Not Required. Work/Hygiene Practices: Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply.