



GS1025

ZONE 1,2,3



LOW ODOR FLOOR FINISH

A revolutionary multi-speed floor finish designed to provide **wet-look** gloss levels. Formulated with advanced zinc-free acrylic polymers and top quality waxes. GS 40 certified

FORMULA FEATURES

This product meets the Green Seal™ environmental standard for industrial and institutional cleaners based on its reduced human and aquatic toxicity and reduced smog production potential.



- ▶ High Gloss
- ▶ Non-yellowing
- ▶ Zinc-Free
- ▶ Durable
- ▶ May be Utilized with Equipment Ranging from 1000-2600 rpms

APPLICATIONS *READY TO USE

- ▶ For use on resilient tile, and terrazzo floors to protect and provide long-lasting gloss levels. Designed for use in high-speed environmentally sensitive maintenance programs.
- ▶ For facilities with one to six burnishing per week average.

AREAS OF UTILIZATION

- ▶ Schools
- ▶ Hospitals
- ▶ Nursing Homes
- ▶ Office Buildings
- ▶ Universities
- ▶ Institutions
- ▶ Grocery Stores
- ▶ Department Stores
- ▶ Restaurants
- ▶ Manufacturing Facilities

OTHER FINE FLOOR CLEANER/STRIPPER FORMULAS

- ▶ HUSKY 1000 Semi-Permanent Resilient Floor & Concrete Sealer
- ▶ HUSKY 1001 Versatile Premium Floor Sealer
- ▶ HUSKY 1018 High Gloss Economy Floor Finish
- ▶ HUSKY 1020 High Gloss Premium Floor Finish
- ▶ HUSKY 1025 High Performance UHS Premium Floor Finish
- ▶ HUSKY 1030 High Solids Premium Floor Finish
- ▶ HUSKY 1041 Multi Purpose Rejuvenator
- ▶ HUSKY GS1018 Floor Sealer/Finish

OTHER LIQUID/AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Odor Control
- ▶ Industrial Care
- ▶ Specialty Products
- ▶ Skin Care
- ▶ Health Care
- ▶ Carpet Care

CANBERRA CORPORATION ▶ 3610 Holland-Sylvania Rd. ▶ Toledo, Ohio 43615
(419) 841-6616 ▶ fax: (419) 841-7597 ▶ Visit Our Website: www.canberracorp.com/

GS1025 LOW ODOR FLOOR FINISH

DIRECTIONS

PRODUCT DATA



1. Before applying floor finish, make sure that the floor surface is properly prepared. If the floor has been stripped, all residual stripper should be removed and the pH of the floor should be returned to neutral (6.5-7.5).



2. Always apply thin coats using a clean mop. It is important to pass the mop head in a figure 8 pattern to ensure that all areas are thoroughly covered.



3. Allow floor finish to dry sufficiently before walking on it or applying additional coats. For standard conditions, allow at least 30-45 minutes. For thorough drying in poor ventilation areas, dry times may be extended.


4. Repeat steps two and three for additional coats.

Acrylic Polymer Base
 UHS Repairable
 Removes Easily
 Slip Resistant
 Superior Adhesion
 Superior Color
 DOT Regulated
 GS 40 Certified
 Zinc-Free

YES	NO
X	
X	
X	
X	
X	
X	X
X	
X	

Maintenance/Formula/Facility Recommendation Matrix

Zone	Maintenance	Facility Recommendation	Formula
ZONE 1	Low Maintenance • Less than one buff or burnishing per week. • Customer typically wants a gloss level (7-9) to hold for extended period. Gloss Level: Initial: 7-8 • Post-Burnish: 8-9	Classrooms Budget/Staff Constrained Facility Restaurant Bars C-Stores	1018
ZONE 2	Intermediate Maintenance • One to five buff or burnishings per week. • Customer expects good initial gloss level with good repairability. Gloss Level: Initial: 6-8 • Post-Burnish: 8-10	Nursing Homes, Colleges Long Term Care Facilities Regional Medical Centers Urgent Care Facilities Government Offices, Grocery Stores Larger Restaurants, Drug Stores Retail Shops, Strip Malls	GS1018, 1020, GS1025, 1022, 1030
ZONE 3	High Maintenance • Five or more buff or burnishings per week. • Customer demands repairability with critically high gloss levels. Gloss Levels: Initial: 9 • Post-Burnish: 9-10	Hospitals, Supermarkets Office Lobbies, Show Rooms Museums, Universities Shopping Malls, Mega/Super Stores	1025



HAZARD RATING
 4 = Extreme
 3 = High
 2 = Moderate
 1 = Slight
 0 = Insignificant

SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#'s	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Water	7732-18-5	N/A	N/A	N/A	>78
Tributoxyethyl phosphate	78-51-3	N/A	N/A	N/A	<2
Diethylene glycol ethyl ether	111-90-0	N/A	N/A	N/A	<2
Polyacrylate copolymer	N/A	N/A	N/A	N/A	15-20
Oxidized polyethylene	68441-17-8	N/A	N/A	N/A	<4

* This chemical is subject to the reporting requirements for section 313 of title III of the superfund amendments and reauthorization act of 1986 and 40 CFR part 372.

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	~212° F	Specific Gravity (H ₂ O=1)	1.030
Vapor Pressure (mm Hg.)	N/E	Percent Volatile By Weight (%)	78%
pH (conc.)	8.6	Evaporation Rate (H ₂ O=1)	~1
Solubility in Water	Complete		
Appearance and Odor	White Liquid/Mild Fragrance		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): None Flammable Limits: LEL: N/A UEL: N/A
 Extinguishing Media: Water, CO₂, Foam or media suitable for surrounding fire
 Special Fire Fighting Procedures: Standard fire fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus.
 Unusual Fire and Explosion Hazards: None Known

SECTION V - PHYSICAL HAZARDS

Stability	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid: None Known
Incompatibility (Materials to Avoid):	Do not mix with other chemicals.	
Hazardous Decomposition Products or By-products:	Thermal decomposition or burning may produce toxic vapors or gases.	
Hazardous	<input type="checkbox"/> May Occur	Conditions to Avoid: None Known
Polymerization	<input checked="" type="checkbox"/> Will Not Occur	

N/A (Not applicable / Not available)
 N/E (Not Established)

SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? Skin? X Ingestion? X

Health Hazards (1. Acute and 2. Chronic) 1. Acute: Harmful if swallowed. Eye irritant.

2. Chronic: None Known

Chemical Listed as Carcinogen or Potential Carcinogen:

National Toxicology Program: No No

I.A.R.C. Monographs: No

OSHA: No

Signs and Symptoms of Exposure: Irritation or burning sensation.

Medical Conditions Generally Aggravated by Exposure: May aggravate skin disorders or respiratory ailments. Emergency and First Aid Procedures: Eye Contact: Flush immediately with water for 15 minutes. Get medical attention. Skin Contact: Flush with water for 15 minutes. Remove and wash contaminated clothing. Ingestion: Rinse mouth with water. Then drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.

Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.

Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not expected to be necessary under normal conditions of use. Where exposure cannot be adequately controlled by general or local ventilation, use appropriate respiratory protection to prevent over exposure. An approved dust/mist respirator would be recommended. Ventilation: Local Exhaust: As Necessary Mechanical (General): Adequate Special: N/A Other: N/A Protection Gloves: Water Impervious (Latex, Neoprene) Eye Protection: Chemical Resistant Goggles
 Other Protective Clothing Or Equipment: Not Required. Work/Hygiene Practices: Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply.