

A semi-permanent resilient tile floor and concrete sealer with excellent penetration, quickly fills pores and seals resilient tile floors. This easy to use, diamond-tough, acrylic based floor sealer levels beautifully, providing exceptional durability, protection, and adhesion properties. This sealer can be removed using a special stripper at specified use dilution. Resists stains that would otherwise mar unprotected floors, such as iodine, betadine, mustard, catsup, coffee, tea, chocolate, rust, kool-aid and other dyed products. Excellent chemical resistance.

**THE
NEXT LEVEL**
in CLEANING & MAINTENANCE

DIRECTIONS FOR USE

Initial Application

1. Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well and allow to dry.
2. Using a clean mop, sprayer, roller, or lamb's wool applicator, apply sealer in a thin, uniform coat. Allow to dry thoroughly, (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
3. Allow floor to dry completely, then apply floor finish in thin, uniform coats.

Day-To-Day Maintenance

1. Keep floor clean and free from dust and grit for maximum durability.
2. Maintain finish with appropriate method. See finish label for direction.

PERFORMANCE DATA

Approximate Coverage 2000-2500 sq. ft./gal.
 Adhesion Excellent
 Finish Compatibility Excellent
 Water Resistance Excellent
 Detergent Resistance Excellent
 Permanent Yes, can only be removed with special strippers.
 Application Resilient Tile Floors Quarry Terrazzo Floors Sealed Wood Floors Many Kinds of Concrete Floors

SAFETY DATA CAUTION: Contains Dibutylphthalate. Keep out of reach of children. Do not swallow. May cause nausea. See Material Safety Data Sheet for further information.

FIRST AID: For eye contact, flush eye well with water and call a physician. If swallowed, get immediate medical attention.

WARNING: Water or other foreign substances will cause any seal to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present. NOTE: To avoid product contamination, do not return any

Manufactured By:
CANBERRA CORPORATION
 3610 Holland-Sylvania Rd.
 Toledo, Ohio 43615

 College of Knowledge
 IEHA Certified Training &
 Education Available on CD ROM

unused material to original container.

SPECIAL INSTRUCTIONS


Engineered for safety... this seal utilizes special slip resistant additives for superb snubbing action. Exceeds industry standards for static coefficient of friction (ASTM2047/82).

Contains:
 Water CAS# 7732-18-5, Polyacrylate CAS# 9003-01-4, Glycol ether DB CAS# 112-34-5, Dibutylphthalate CAS# 84-74-2, Ethylene Glycol CAS# 107-21-1.

CLASSIFIED FLOOR COATING AND FINISHING MATERIAL
UL AS TO SLIP RESISTANCE ONLY 13X2

HUSKY 1000 SEMI-PERMANENT RESILIENT FLOOR AND CONCRETE SEALER Eye and skin irritant. Contains a suspected teratogen. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep out of reach of children. If in contact with eyes, flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.** Irritant pour les yeux et la peau. Contient une substance que l'on soupçonne tératogène. Éviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Garder hors de la portée des enfants. En cas de contact avec les yeux, laver à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver immédiatement à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, consulter un médecin immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT.**
CANBERRA CORPORATION

Made in U.S.A.
For Industrial and Institutional Use Only
Keep From Freezing

 This container is coded for Recycling



1000

**SEMI-PERMANENT
 RESILIENT FLOOR &
 CONCRETE SEALER**

**A Semi-Permanent Floor Seal with
 Exceptional Durability, Protection,
 Leveling, and Adhesion Properties.**

CAUTION:
 Keep Out of Reach of Children
 See back panel for additional precautionary information.
 Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

