

FOR TERRAZZO AND RESILIENT TILE!
FORMULATED WITH DURAPLUS® Highly acclaimed,
internationally accepted, patented polymer system.
MULTIPLE SUBSTRATE COMPATIBILITY!
Seals terrazzo, vinyl, vinyl composition and
other resilient tile. Excellent adhesion and
compatibility with other finishes.

CUTTING EDGE TECHNOLOGY
Made with the most advanced floor sealer
polymers available. A solid base coat for
premium finishes, providing low color, high
depth-of-gloss results on terrazzo, travertine,
marble, asphalt tile, vinyl composition, linoleum
and other resilient floors.

DIRECTIONS FOR USE

Initial Application

1. Remove all old finish from floor. For new floors, stripping of
factory applied finish is necessary. Rinse well and allow to dry.
2. Using a clean mop, apply sealer in a thin, uniform coat. Allow
to dry thoroughly, (30 to 40 minutes). For very porous floors
and higher base gloss, a second uniform coat should be
applied.
3. Allow floor to dry completely, then apply floor finish in thin,
uniform coats.

NOTE: To avoid product contamination, do not return any unused
material to original container.

Day-To-Day Maintenance

1. Keep floor clean and free from dust and grit for maximum
durability.
2. Maintain finish with appropriate method. See finish label for
direction.

SAFETY DATA CAUTION: Keep out of reach of children. Do not
swallow. May cause nausea. See Material Safety Data Sheet for
further information.

FIRST AID: For eye contact, flush eye well with water and call a
physician. If swallowed, get immediate medical attention.

NOTE: Water or other foreign substances will cause any seal to
become slippery. **ALWAYS** use a "Wet Floor" sign when moisture
is present.

Manufactured By:
CANBERRA CORPORATION
3610 Holland-Sylvania Rd.
Toledo, Ohio 43615

SPECIAL INSTRUCTIONS
Engineered for safety. Exceeds industry standards for static coefficient
of friction (ASTM2047/82).

Contains:

Water CAS# 7732-18-5, Polyacrylate CAS# 25987-
66-0, Glycol Ether CAS# 111-90-0,
Dibutylphthalate CAS# 84-74-2, TBEP CAS# 78-
51-3.

THE
NEXT LEVEL
in **CLEANING & MAINTENANCE**


HUSKY 1001 VERSATILE PREMIUM FLOOR SEALER Eye
and skin irritant. Contains a suspected teratogen. Avoid contact
with eyes and skin. Wear suitable protective clothing. Keep out
of reach of children. If in contact with eyes, flush with water for
15 minutes. Call a doctor if irritation persists. If in contact with
skin, flush with water. Call a doctor if irritation develops. If ingested, do
not induce vomiting. Call a doctor immediately. **READ MATERIAL
SAFETY DATA SHEET BEFORE USING PRODUCT.**

Irritant pour les yeux et la peau. Contient une substance que l'on
soupçonne tératogène. Éviter le contact avec les yeux et la peau. Porter
un vêtement de protection approprié. Garder hors de la portée des enfants.
En cas de contact avec les yeux, laver à grande eau durant 15 minutes.
Appeler un médecin si l'irritation persiste. En cas de contact avec la peau,
laver immédiatement à grande eau. Appeler un médecin en cas d'irritation.
En cas d'ingestion, ne pas tenter de faire vomir, consulter un médecin
immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER
CE PRODUIT.**

CANBERRA CORPORATION

Made in U.S.A.
For Industrial and Institutional Use Ony
Keep From Freezing

011703



1001

**VERSATILE PREMIUM
FLOOR SEALER**

**A Multi-Substrate Premium
Floor Sealer**

**Keep Out of Reach of Children
CAUTION**

See back panel for additional precautionary information.

Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

