

**HIGH DURABILITY AND EXTREME GLOSS!**

High Solids Premium Formula means less coats, less work, and lower total cost of application!

**MULTIPLE MAINTENANCE PLATFORMS!** Propane burnishable, UHS burnishable, mid-speed and spray buffable. Excellent durability and gloss in one product.

**CUTTING EDGE TECHNOLOGY**

Made with the most advanced floor finish polymers available. Excellent reparability, re-coat, slip, water, detergent and black heel mark resistance. Repairs all types of equipment. Product is non-yellowing. Designed for all types of resilient tile.

**DIRECTIONS FOR USE**

**Initial Application**

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a uniform coat of finish. Allow to dry thoroughly (30 to 40 minutes) or as ambient conditions dictate. Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

**NOTE:** To avoid product contamination, do not return any unused material to original container.

**Day-To Day Maintenance**

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. After cleaning, burnish floor as needed to maintain gloss. Use only ultra high speed buffing pads.

**SAFETY DATA**

**CAUTION:** Keep out of reach of children. Do not swallow. May cause nausea. See Material Safety Data Sheet for further information. **FIRST AID:** For eye contact, flush eye well with water and call a physician. If swallowed, get immediate medical attention.

**NOTE:** Water or other foreign substances will cause any floor finish to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present.

**SPECIAL INSTRUCTIONS:**

Engineered for safety. Exceeds industry standards for static coefficient of friction (ASTM 2047/82).

**CONTAINS:** Water CAS# 7732-18-5, Glycol ether CAS# 34590-94-8, Polyacrylate CAS# 25987-66-0, P/E Wax CAS# 68441-17-8, Glycol Ether CAS# 111-90-0.

**THE  
NEXT LEVEL**  
in **CLEANING & MAINTENANCE**

**HUSKY 1030 HIGH SOLIDS PREMIUM FLOOR FINISH** Eye and skin irritant. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep out of reach of children. If in contact with eyes, flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Irritant pour les yeux et la peau. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Garder hors de la portée des enfants. En cas de contact avec les yeux, laver à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement.

**LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT.**  
**CANBERRA CORPORATION**

Made in U.S.A.  
For Industrial and Institutional Use Only  
Keep From Freezing



College of Knowledge  
IEHA Certified Training &  
Education Available on CD ROM

081806



Manufactured By:  
**CANBERRA CORPORATION**  
3610 Holland-Sylvania Rd.  
Toledo, Ohio 43615



**1030**

**CAN BE USED AS A  
SEALER & FINISH**

# HIGH SOLIDS PREMIUM FLOOR FINISH

Designed For Intermediate  
Maintenance Floor Care Programs.

Keep Out of Reach of Children  
**CAUTION**

See back panel for additional precautionary information.  
Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

