



(Oil Based)

1205



DUST MOP TREATMENT

An easy-to-use product to control dust on most surfaces. Spray on dusting tool with our "fine-mist" delivery system and prevent dust from remaining or scattering. Reduces airborne dust when cleaning which protects the built environment and extends the life of floor finish. When replacing HVAC filters apply this formula to the new filters before installing to enhance filter performance.

FORMULA FEATURES

- ▶ Pleasant Lemon Fragrance
- ▶ Designed for a Variety of Surfaces
- ▶ "Fine-mist" Delivery System
- ▶ Attracts and Holds Dust
- ▶ Prevents Dust from Scattering
- ▶ May be Applied to all Dusting Tools & HVAC Filters

APPLICATIONS *READY TO USE

- ▶ Designed for use on all types and sizes of dust mops and dusting tools to attract and hold dust

AREAS OF UTILIZATION

- ▶ Linoleum Floors
- ▶ Venetian Blinds
- ▶ Window Frames
- ▶ Wood
- ▶ Plastics
- ▶ Formica
- ▶ Concrete
- ▶ Composition Floors
- ▶ Furniture
- ▶ Auto Interiors
- ▶ HVAC Filters
- ▶ Vinyl Tile

OTHER FINE AEROSOL FORMULAS

- ▶ HUSKY 1200 Furniture Polish (Lemon Oil Fortified)
- ▶ HUSKY 1202 Fresh Linen Scent Air Freshener & Neutralizer
- ▶ HUSKY 1207 Gelled Baseboard Stripper
- ▶ HUSKY 1210 Stainless Steel Cleaner Polish
- ▶ HUSKY 1211 Stainless Steel Cleaner & Polish (Oil Based)
- ▶ HUSKY 1220 Glass, Plastic & CRT Cleaner
- ▶ HUSKY 1225 All Purpose Spray & Wipe
- ▶ HUSKY 1229 Vandalism Mark & Stain Remover
- ▶ HUSKY 1230 Disinfectant Deodorant
- ▶ HUSKY 1240 Foaming Disinfectant Cleaner
- ▶ HUSKY 1250 Chewing Gum Remover
- ▶ HUSKY 1255 Foaming Oven & Grill Cleaner (Heavy Duty Formula)
- ▶ HUSKY 1260 Flying Insecticide (Pleasantly Scented)
- ▶ HUSKY 1270 Residual Insecticide (For Crawling Insects)
- ▶ HUSKY 1280 Wasp & Hornet Insecticide

OTHER LIQUID/AEROSOL FORMULA CATEGORIES


- ▶ Restroom Care
- ▶ Odor Control
- ▶ Industrial Care
- ▶ Specialty Products
- ▶ Skin Care
- ▶ Health Care
- ▶ Carpet Care

CANBERRA CORPORATION ▶ 3610 N. Holland-Sylvania Rd. ▶ Toledo, Ohio 43615
(419) 841-6616 ▶ fax: (419) 841-7597 ▶ Visit Our Website: www.canberracorp.com

Oil Based 1205 DUST MOP TREATMENT


DIRECTIONS

PRODUCT DATA



1. Spray treatment on dust mop at rate of 1/2 to 1 ounce per six inch length of mop. Allow to air dry. Launder mops periodically, as required by soil conditions. Launder all previously treated oil mops before applying a water based mop treatment.

Can Size: 20 oz. Aerosol
 Net Weight: 14 oz.
 Color: Clear, oily liquid
 Fragrance: Lemon
 Propellant: Hydrocarbon
 Spray Pattern: Misty Solid Cone



SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#'s	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Heavy Alkylate Naphtha	64741-65-7	500	100*	>25ml/kg	5-10
Light Mineral Oil	8042-47-5	NE	5mg/m3	NE	5-10
Isoparaffinic Solvent	64742-47-8	ND	ND	NA	60-70
Liquified Petroleum Gas	68476-85-7	1000	1000	NE	15-20

*This chemical is subject to the reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point.....	N/A	Specific Gravity (H ₂ O=1)	< 1
Vapor Pressure (psig) ...	115 @ 130°F	Percent Volatile By Weight (%) ...	>99
pH (conc.).....	N/A	Evaporation Rate (H ₂ O=1).....	<1
Solubility in Water.....	Negligible		
Appearance and Odor	Colorless Liquid, Lemon Fragrance		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): Flammable **Flammable Limits: %volume in air** LEL: 2.1 UEL: 9.5
Extinguishing Media: Carbon dioxide, Foam or media suitable for surrounding fire
Special Fire Fighting Procedures: Cool containers. Use equip. or shielding, as required, to protect personnel from bursting, rupturing or venting containers.
Unusual Fire and Explosion Hazards: At elevated temp. (over 54C-130°F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - PHYSICAL HAZARDS

Stability Unstable
 Stable
Incompatibility (Materials to Avoid): Oxidizing agents.
Hazardous Decomposition Products or By-products: Thermal decomposition or burning may produce toxic vapors or gases.
Hazardous May Occur **Conditions to Avoid:** Do not store above 54C-130°F
Polymerization Will Not Occur Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

N/A (Not applicable / Not available)

N/E (Not Established)

111510

SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? X Eyes? X Skin? X
 Ingestion? X

Health Hazards (1. Acute and 2. Chronic) 1. Acute: Harmful if swallowed. Eye & skin irritant.
2. Chronic: None Known

Chemical Listed as Carcinogen or Potential Carcinogen:

National Toxicology Program: No
 I.A.R.C. Monographs: No
 OSHA: No

Signs and Symptoms of Exposure: Inhalation may cause dizziness and drowsiness. Irritation
Medical Conditions Generally Aggravated by Exposure: Preexisting skin or eye disorders may be aggravated by exposure. **Emergency and First Aid Procedures: Eye Contact:** Flush immediately with water for 15 minutes. Get medical attention. **Skin Contact:** Flush with water for 15 minutes. Remove and wash contaminated clothing. **Ingestion:** Get immediate medical attention. Note to physician: Product contains app. 80% petroleum distillate. **Inhalation:** Remove victim to fresh air. Artificial respiration if needed. Get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Remove all sources of ignition and ventilate area. Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.

Waste Disposal Method: Do not puncture or incinerate containers. Dispose of container in accordance with local, state and federal regulations.

Precautions To Be Taken In Handling And Storing: Avoid breathing vapor. Keep away from heat or flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temp. above 130°F (54C). Store as Level 3 Aerosol (NFPA 30B).
Other Precautions: Read & follow directions on product label; they are your best guide to using this product in most effective way, and give necessary safety precautions to protect your health.
Store as level 3 Aerosol (NFPA 30B)

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (sec. II), use NIOSH approved respirator to prevent overexposure. **Ventilation:** Local exhaust is adequate under normal conditions, mechanical ventilation is optional. **Local Exhaust:** As necessary **Mechanical (General):** Adequate **Special:** N/A **Other:** N/A **Protection Gloves:** Optional: Chemical resistant gloves **Eye Protection:** Chemical safety glasses are recommended. **Other Protective Clothing Or Equipment:** Wear impervious clothing to prevent skin contact. **Work/Hygiene Practices:** Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply. Wash thoroughly after handling.