



oil based

# 1211



## STAINLESS STEEL CLEANER & POLISH

This premium oil based formula is designed to clean, polish and protect stainless steel and a wide variety of other surfaces quickly. Will not leave behind an oily residue but will resist fingerprints, grease and water spatter with a protective coating. The fine mist spray has a light foam application allowing the proper amount of product for the cleaning job. Avoid overspray on flooring as surfaces may become slippery.

### FORMULA FEATURES

- ▶ Oil Based
- ▶ No Build-Up
- ▶ Easy to Use
- ▶ Resists Finger Prints
- ▶ Cleans and Protects Surfaces
- ▶ No Oily Residue

### APPLICATIONS \*READY TO USE

- ▶ Cleans, polishes and protects stainless steel and most other metal surfaces without hard rubbing.

### AREAS OF UTILIZATION

- ▶ Dishwashers
- ▶ Trims
- ▶ Chrome
- ▶ Doors
- ▶ Freezers
- ▶ Formica
- ▶ Refrigerators
- ▶ Windows
- ▶ Escalators
- ▶ Ceramics
- ▶ Elevators
- ▶ Porcelain/Tile

### OTHER FINE AEROSOL FORMULAS

- ▶ HUSKY 1200 Furniture Polish (Lemon Oil Fortified)
- ▶ HUSKY 1202 Fresh Linen Scent Air Freshener & Neutralizer
- ▶ HUSKY 1205 Dust Mop Treatment (Oil Based)
- ▶ HUSKY 1207 Gelled Baseboard Stripper
- ▶ HUSKY 1210 Stainless Steel Cleaner Polish
- ▶ HUSKY 1220 Glass, Plastic, & CRT Cleaner
- ▶ HUSKY 1225 All Purpose Spray and Wipe
- ▶ HUSKY 1229 Vandalism Mark & Stain Remover
- ▶ HUSKY 1230 Disinfectant Deodorant
- ▶ HUSKY 1240 Foaming Disinfectant Cleaner
- ▶ HUSKY 1250 Chewing Gum Remover
- ▶ HUSKY 1255 Foaming Oven & Grill Cleaner (Heavy Duty Formula)
- ▶ HUSKY 1260 Flying Insecticide (Pleasantly Scented)
- ▶ HUSKY 1270 Residual Insecticide (For Crawling Insects)
- ▶ HUSKY 1280 Wasp & Hornet Insecticide

### OTHER LIQUID/AEROSOL FORMULA CATEGORIES


- ▶ Restroom Care
- ▶ Odor Control
- ▶ Health Care
- ▶ Carpet Care
- ▶ Skin Care
- ▶ Floor Care
- ▶ Industrial Care

CANBERRA CORPORATION ▶ 3610 N. Holland-Sylvania Rd. ▶ Toledo, Ohio 43615  
(419) 841-6616 ▶ fax: (419) 841-7597 ▶ Visit Our Website: [www.canberracorp.com](http://www.canberracorp.com)

# Oil Based 1211 STAINLESS STEEL CLEANER & POLISH

## DIRECTIONS

## PRODUCT DATA




1. Hold can upright. Press button and spray a small area until wet. Use sparingly. Clean with one cloth and polish with a second clean, dry cloth. The gloss is renewed and will be retained. The cleaning process is simple. No rubbing is required. Not to be used on cooking utensils, such as pots, pans, knives, forks or spoons.



Avoid overspray on flooring as surface may become slippery!

|                |   |
|----------------|---|
| Can Size:      | 20 oz. Aerosol  |
| Net Weight:    | 15 oz.  |
| USDA           | A7 + C1 Equivalent  |
| Color:         | Clear   |
| Odor:          | Lemon   |
| Propellant:    | Hydrocarbon   |
| Spray Pattern: | Wet, Hollow Cone  |
| Flammability:  | Flammable as per<br>CPSC Flame Extension<br>Test as described in<br>16 CFR 1500.45. |



### SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

| Hazardous components                | CAS#s      | WT.%       | PEL     | TWA-TLV      |
|-------------------------------------|------------|------------|---------|--------------|
| Synthetic Isoparaffinic Hydrocarbon |            | 64742-47-8 | 10-30   | 152ppm NE/NE |
| Mineral Spirits*                    | 64742-48-9 | 10-30      | 177ppm  | 177ppm       |
| Acetone                             | 67-64-1    | 10-30      | 1000ppm | 500ppm       |
| Methyl Acetate                      | 79-20-9    | 1-10       | 200ppm  | 200ppm       |
| Propane                             | 74-98-6    | 10-30      | 1000ppm | 1000ppm      |

\*This Chemical is subject of the reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

### SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

|                               |   |   |      |
|-------------------------------|---|---|------|
| Boiling Point.....            | N/A                                     | Specific Gravity (H <sub>2</sub> O=1) ..... | <1.0 |
| Vapor Pressure (mm Hg.) ..... | 60 psig at 130°F                        | Vapor Density (Air = 1) .....               | >1   |
| pH .....                      | N/A                                     | Evaporation Rate (Ether=1).....             | <1   |
| Solubility in Water.....      | Negligible                              |   |      |
| Appearance and Odor .....     | Aerosol spray with characteristic odor. |   |      |

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Aerosol Flammability:** Flammable as described by 16 CFR 1500.45.  
**Flammable Limits:** LEL: 1.8 UEL: 9.2  
**Extinguishing Media:** CO<sub>2</sub>, Foam or dry chemical  
**Special Fire Fighting Procedures:** Containers should be cooled with water to prevent pressure build-up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers. **Unusual Fire and Explosion Hazards:** Heated cans may burst.

### SECTION V - PHYSICAL HAZARDS

|   |  |
|---|--|
| Stability <input type="checkbox"/> Unstable<br><input checked="" type="checkbox"/> Stable                         | <b>Conditions to Avoid:</b> Do not store above 54C-130°F. Keep away from heat, direct sunlight, open flames or sparks. Dropping containers may cause bursting. |
| <b>Incompatibility (Materials to Avoid):</b> Oxidizing agents.  |  |
| <b>Hazardous Decomposition Products or By-products:</b> Toxic chemicals may be formed in small amounts.           |  |
| Hazardous <input type="checkbox"/> May Occur<br>Polymerization <input checked="" type="checkbox"/> Will Not Occur |  |

N/A (Not applicable / Not available)  
N/E (Not Established)

111510

### SECTION VI - HEALTH HAZARDS

**Route(s) of Entry:** Inhalation? X Skin? X Ingestion? X  
**Health Hazards** (1. Acute and 2. Chronic) **1. Acute:** Harmful if swallowed. Eye and skin irritant.  
**2. Chronic:** None Known

#### Chemical Listed as Carcinogen or Potential Carcinogen:

|                              |  |
|------------------------------|--|
| National Toxicology Program: | <input checked="" type="checkbox"/> No |
| I.A.R.C. Monographs:         | <input checked="" type="checkbox"/> No |
| OSHA:                        | <input checked="" type="checkbox"/> No |

**Signs and Symptoms of Exposure:** Irritation, defatting of skin on prolonged contact. High vapor concentrations may result in depression, headache, dizziness, nausea. Vomiting which could cause aspiration pneumonia.

**Emergency and First Aid Procedures:** **Eye Contact:** Flush with large quantities of water, seek medical attention if irritation occurs. **Skin Contact:** Remove and wash contaminated clothing before reuse. Wash affected areas with soap and water, seek medical attention if irritation occurs. **Ingestion:** Seek medical attention. **Inhalation:** Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**Steps To Be Taken In Case Material Is Released Or Spilled:** Remove all sources of ignition and ventilate area. Mop up or otherwise absorb and hold for disposal.  
**Waste Disposal Method:** Dispose of in accordance with local, state and federal regulations. Do not puncture or incinerate containers.  
**Precautions To Be Taken In Handling And Storing:** Keep away from heat or flame. Avoid breathing vapors. Keep out of reach of children. For use by trained personnel only. Use with adequate ventilation. **Store as level 3 Aerosol (NFPA 30B) Other Precautions:** Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

### SECTION VIII - CONTROL MEASURES

**Respiratory Protection:** None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure. **Ventilation:** Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limits. **Local Exhaust:** As Required  
**Protection Gloves:** Chemical resistant. **Eye Protection:** Chemical safety glasses recommended.  
**Work/Hygiene Practices:** Ensure strict sanitary conditions are conformed to when using chemicals.