



1229



VANDALISM MARK & STAIN REMOVER

Engineered specifically to remove vandal marks from a variety of surfaces. A unique blend of solvents are used to remove crayon, pencil, ink, spray paint and lipstick. Also ideal for removing tape residue scuff marks and waxes. Care should be taken when using on synthetic surfaces such as rubber, asphalt tile and plastics. Try first on small hidden area.

FORMULA FEATURES

- ▶ Easy-to-use
- ▶ Removes Crayon, Lipstick
- ▶ Engineered to remove Spray Paint
- ▶ Works on Oil Based Marks
- ▶ Superior Blend of Solvents
- ▶ Heavy, Wet Application

APPLICATIONS *READY TO USE

- ▶ Spray directly on marked or stained surfaces, let stand, then wipe or rinse off. For difficult marks, spray again and use a stiff brush to agitate the area.

AREAS OF UTILIZATION

- ▶ Steel
- ▶ Aluminum
- ▶ Enamel
- ▶ Brick
- ▶ Tile
- ▶ Formica
- ▶ Marble
- ▶ Brass
- ▶ Porcelain
- ▶ Chrome
- ▶ Glass
- ▶ Many Other Surfaces

OTHER FINE AEROSOL FORMULAS

- ▶ HUSKY 1200 Furniture Polish (Lemon Oil Fortified)
- ▶ HUSKY 1202 Fresh Linen Scent Air Freshener & Neutralizer
- ▶ HUSKY 1205 Oil Based Dust Mop Treatment
- ▶ HUSKY 1207 Gelled Baseboard Stripper
- ▶ HUSKY 1210 Stainless Steel Cleaner Polish
- ▶ HUSKY 1211 Stainless Steel Cleaner & Polish (Oil Based)
- ▶ HUSKY 1220 Glass, Plastic & CRT Cleaner
- ▶ HUSKY 1225 All Purpose Spray & Wipe
- ▶ HUSKY 1230 Disinfectant Deodorant
- ▶ HUSKY 1240 Foaming Disinfectant Cleaner
- ▶ HUSKY 1250 Chewing Gum Remover
- ▶ HUSKY 1255 Foaming Oven & Grill Cleaner (Heavy Duty Formula)
- ▶ HUSKY 1260 Flying Insecticide (Pleasantly Scented)
- ▶ HUSKY 1270 Residual Insecticide (For Crawling Insects)
- ▶ HUSKY 1280 Wasp & Hornet Insecticide


OTHER LIQUID/AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Specialty Products
- ▶ Carpet Care
- ▶ Odor Control
- ▶ Skin Care
- ▶ Health Care
- ▶ Floor Care

CANBERRA CORPORATION ▶ 3610 N. Holland-Sylvania Rd. ▶ Toledo, Ohio 43615
(419) 841-6616 ▶ fax: (419) 841-7597 ▶ Visit Our Website: www.canberracorp.com

1229 VANDILISM MARK & STAIN REMOVER

DIRECTIONS



1. SHAKE WELL BEFORE USING. Remove outer cap. Hold can in upright position. Point valve opening toward area to be cleaned. Press button and spray a small area until wet. Let stand for several seconds. Wipe off with clean dry cloth. Rinse, if desired. Use stiff brush to agitate difficult marks.



IMPORTANT:

Care should be taken when using on synthetic surfaces such as rubber, asphalt tile and plastics.

Try first on small hidden area.

PRODUCT DATA

Can Size:	20 oz. Aerosol
Net Weight:	18 oz.
USDA	C1 Equivalent
Color:	Clear
Fragrance:	Chlorinated
Propellant:	Hydrocarbon
Spray Pattern:	Wet Forceful Spray
Flammability:	Flammable as per CPSC Flame Extension Test as described in 16 CFR 1500.45.



SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#'s	WT.%	PEL	ACGIH
Dichloromethane	75-09-2	40-50	25ppm	50ppm
Tetrachloroethylene	127-18-4	8-10	100	25
Toluene	108-88-3	10-15	200	50
Propylene Oxide	75-56-9	0.1-0.5	100	2
Propane	74-98-6	8-10	NE	1000

*This Chemical is subject to the reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization of 1986 and 40 CFR Part 372

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point102.2°F	Specific Gravity (H ₂ O=1)0.893
Vapor Pressure (mm Hg.)	...25-35 psig at 70°F	Vapor Density (Air = 1)>1
pHN/A	Evaporation Rate (Ether=1)<1
Solubility in WaterNegligible		
Appearance and OdorWet spray, Chlorinated odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Flammable as described by 16 CFR 1500.45.
Flammable Limits: LEL: 1.8 UEL: 9.2
Extinguishing Media: CO₂, Foam or dry chemical
Special Fire Fighting Procedures: Containers should be cooled with water to prevent pressure build-up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers. **Unusual Fire and Explosion Hazards:** At elevated temp. (over 54°C-130°F) containers exposed to direct flame or heat contact should be cooled w/water to prevent weakening of container structure.

SECTION V - PHYSICAL HAZARDS

Stability	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid: Do not store above 54°C-130°F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.
Incompatibility (Materials to Avoid):	Oxidizing agents.	
Hazardous Decomposition Products or By-products:	Toxic chemicals may be formed in small amounts.	
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	

N/A (Not applicable / Not available)
N/E (Not Established)

5-09

SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? X Eyes? X Skin? X Ingestion? X
Health Hazards (1. Acute and 2. Chronic) **1. Acute:** Harmful if swallowed. Eye and skin irritant.
2. Chronic: Chronic exposure to methylene chloride & perchloroethylene has caused liver toxic effects in experimental animals.
Chemical Listed as Carcinogen or Potential Carcinogen:
 National Toxicology Program: Yes No
 I.A.R.C. Monographs: Yes No
 OSHA: Yes No
Signs and Symptoms of Exposure: Irritation, burning, dizziness.
Emergency and First Aid Procedures: Eye Contact: Flush with large quantities of water, seek medical attention if irritation occurs. **Skin Contact:** Remove contaminated clothing. Flush skin with water, follow by washing with soap and water. If irritation occurs, get medical attention Do not reuse clothing until cleaned. **Ingestion:** Seek medical attention. **Inhalation:** Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Remove all ignition sources. Ventilate area. Mop up or otherwise absorb and hold for disposal.
Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Do not puncture or incinerate containers.
Precautions To Be Taken In Handling And Storing: Avoid breathing vapors. Keep out of reach of children. For use by trained personnel only. Use with adequate ventilation. Keep away from heat or flame. Store in cool dry place. **Store as level 1 Aerosol (NFPA 30B)**
Other Precautions: Please read & follow the directions on the product label; they are your best guide to using this product in the most effective way, & give the necessary safety precautions to protect your health.

SECTION VIII - CONTROL MEASURES

Respiratory Protection Non required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure. **Ventilation:** Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limits. **Local Exhaust:** As Required **Protection Gloves:** Chemical Resistant Gloves **Eye Protection:** Chemical Safety glasses recommended. **Work/Hygiene Practices:** Ensure strict sanitary conditions are conformed to when using chemicals. Protective clothing & equipment should be in accordance with 29 CFR 1910.132 & CFR 1910.133.