

FOR INSTITUTIONAL, COMMERCIAL AND INDUSTRIAL USE

READ ENTIRE LABEL CAREFULLY
BEFORE USING PRODUCT.

DIRECTIONS

This effective cleaner is safe to use on porcelain, glass, ceramics, stainless steel, and cast iron surfaces. Keep spray or drippings away from the pilot lights, electrical connections, switches, receptacles, thermostats, heating elements, light bulbs, and other surfaces which might be affected by caustics. Avoid contact with painted or varnished surfaces, clothing, floor tile, linoleum, plastics, chrome, copper, aluminum, and copper-tone surfaces. Not for use on self-cleaning or continuous cleaning ovens. Place newspaper under oven door to protect floor. Wear rubber gloves to avoid skin contact.

1. Use on empty oven, either cold or pre-heated to 200°F and turned off. **TURN OFF PILOT LIGHT and/or ELECTRICAL SWITCH.**

2. Hold can upright and point spray button away from face. SHAKE WELL, then spray inside of oven from a distance of 8 to 12 inches, giving it an even coating.

3. Spray top and bottom of oven first; then spray remaining oven surfaces and allow to stand about 30 minutes. (May be left on overnight with oven door closed.)

4. Wipe oven clean with damp cloth, sponge, or paper towel. Spots that are difficult to remove should be retreated and cleaned with a scouring pad. Rinse with potable water.

5. When clean, re-ignite pilot light, or turn on electric switch, and heat oven to 400°F for 10 minutes before using with food again.

DANGER: When using do not eat, drink or smoke. Use in well ventilated area and avoid breathing vapor. Excessive inhalation will cause irritation of upper respiratory tract and lungs and may cause dizziness or nausea. Do not contact skin, eyes, mucous membranes, and clothing. Contact will cause burns. Do not use near flames or sparks. If swallowed, drink plenty of water or milk. Do not induce vomiting. If inhaled, remove victim to fresh air. If in eyes, immediately flush with plenty of water. If on skin, immediately remove contaminated clothing and flood skin with plenty of water then wash thoroughly with soap and water. In all cases, immediately contact physician. Contents under pressure. Store in a cool, well ventilated area (preferably locked) where temperature will not exceed 120°F (49°C). Do not store in direct sunlight or near surfaces of ignition such as windows, hot surfaces, flames, or sparks. Do not drop, puncture, or incinerate container. Dispose of by replacing cap and wrapping in several layers of newspaper, then discarding in trash. Keep out of reach of children.

CONTAINS (CAS No.): Sodium Hydroxide (1310-73-2), Butyl Carbitol (112-34-5), Octylphenoxy Poly (Ethanoxyl) Ethanol (9002-93-1), Deionized Water (7732-18-5) and Liquefied Petroleum Gas (68476-85-7).

See Material Safety Data Sheet before use!

115150

CONTAINS NO OZONE DEPLETING
CHEMICALS!



College of Knowledge

IEHA Certified Training &
Education Available on CD ROM

Manufactured For:
CANBERRA CORPORATION
3610 Holland-Sylvania Rd.
Toledo, Ohio 43615

#8746P



POINT SPRAY
PATTERN
TOWARDS DOT.



THE
NEXT LEVEL
IN CLEANING & MAINTENANCE

1255

FOAMING OVEN & GRILL CLEANER (HEAVY DUTY FORMULA)

- ▶ Institutional Strength
- ▶ Works in Minutes
- ▶ Quickly Cuts Through:
Heavy Grease /
Baked on Foods /
Carbon
- ▶ VOC Compliant in
all States



DANGER - CORROSIVE
HARMFUL IF SWALLOWED MAY CAUSE BURNS
TO SKIN AND EYES
CONTENTS UNDER PRESSURE
Read carefully other cautions on back panel

NET WT. 20 OZ. (1 LB. 4 OZ.) 567 g