

FOR THE TOUGH STRIPPING JOB...

An extremely powerful stripping compound, formulated specially to quickly remove all types of floor finish and wax build-ups. Removes acrylic, metal cross-linked polymer, carnauba based waxes and floor finishes.

REMARKABLY FAST ACTING... REDUCES TIME AND LABOR COSTS...

The dual detergent system penetrates, re-emulsifies and suspends the very toughest floor finishes, even the highly burnished build-ups. Contains no ammonia or chlorinated solvents. Utilizes a particularly pleasant fragrance not normally found in strippers.

LOW FOAM... SUPERB FOR AUTOMATIC STRIPPERS...

The low foaming characteristics of this product enable it to be used effectively in automatic scrubbers. The remarkably fast chemical action greatly reduces time and labor costs normally required, particularly when the task of stripping is difficult.

GENERAL DIRECTIONS FOR USE

DANGER: Read Carefully

Product must always be diluted. It is important to always wear rubber gloves and have eye protection. Avoid use of product on painted surfaces or wood floors. Use caution when stripping linoleum, asphalt or rubber tile as some bleaching or softening will occur. Test first in a small area. Maintain good ventilation when applying.

1. Dilute 1:10 (12 oz. per gal.) using warm water. First apply to small area to determine amount of time product should be left on surface to acquire best stripping action. Occasionally, solution as strong as 1:1 will be needed for extremely difficult situations.
2. Mop mixed solution on floor and allow to stand approximately 3 minutes. Keep area wet.
3. Machine scrub using stripper pad if needed.
4. Pick up solution with mop or wet vac.
5. Rinse with clear water.

FOR AUTOMATIC SCRUBBERS

Dilution rate will need to be determined by experimenting or by following machine manufacturer's instructions.

Manufactured By:

CANBERRA CORPORATION
3610 Holland-Sylvania Rd.
Toledo, Ohio 43615

THE
NEXT LEVEL
in **CLEANING & MAINTENANCE**

SAFETY DATA DANGER: Harmful or fatal if swallowed. May cause skin or eye damage if not promptly treated. Wear eye protection and resistant (rubber) gloves when handling. May cause respiratory tract irritation, if inhaled. Use only with adequate ventilation. Avoid breathing vapor, spray or mist. If necessary to prevent exposure, wear approved respiratory protection. Combustible

ADDITIONAL PRECAUTION Wet floors are extremely slippery. Keep all pedestrian traffic away from floor until dry.

Contents: sodium hydroxide CAS#1310-73-2, monoethanolamine CAS# 141-43-5 and 2-butoxyethanol CAS# 111-76-2.

HUSKY 705 EXTRA HEAVY DUTY STRIPPER Corrosive material. Combustible liquid. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep away from sources of ignition - no smoking. If in contact with eyes, immediately flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Matière corrosive. Liquide combustible. Éviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Conserver à l'écart de toutes sources d'ignition - ne pas fumer. En cas de contact avec les yeux, laver immédiatement à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT.**

CANBERRA CORPORATION



Made in U.S.A.

For Industrial And Institutional Use Only
Keep From Freezing



This container is coded for Recycling



College of Knowledge

IEHA Certified Training &
Education Available on CD ROM



0 90165 70035 8



705

EXTRA HEAVY DUTY STRIPPER

A High Performance Multi-Surface
Stripper For The Toughest Jobs

DANGER:

Keep Out Of Reach Of Children

See back panel for additional precautionary information.

Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

