



901



SOLVENT BASED INDUSTRIAL CLEANER/DEGREASER

A highly concentrated butyl-based degreaser cleaner designed to remove the heaviest soil buildup. Formulated with a high concentration of solvents and a powerful detergent complex to lift and suspend grease, oils, and other industrial soils. Dilutable for economical cleaning.

FORMULA FEATURES

- ▶ Highly Dilutable for Cost Savings
- ▶ Pleasant Fragrance
- ▶ Powerful Cleaning Action
- ▶ Fast Acting
- ▶ Biodegradable

APPLICATIONS *CONCENTRATED

(Dilute 3 to 12 oz. per gallon of water)

- ▶ For regular cleaning of industrial surfaces to remove heavy buildup of grease, oil, and other soils. Works with automatic scrubbers, pressure washers, mops, and trigger sprayer applications.

AREAS OF UTILIZATION

- ▶ Manufacturing Plants
- ▶ Warehouse Operations
- ▶ Auto Service Operations
- ▶ Machine Shops
- ▶ Trucking Fleet Management
- ▶ Institutions

OTHER HARD WORKING INDUSTRIAL FORMULAS

- ▶ HUSKY 900 Industrial Strength Degreaser
- ▶ HUSKY 902 Non-Butyl Industrial Detergent Complex
- ▶ HUSKY 903 Heavy Duty Foaming Degreaser
- ▶ HUSKY 904 Citrus Plus Foaming Spray & Wipe Cleaner
- ▶ HUSKY 906 O/O RTU Multi-Purpose Cleaner & Degreaser (with HyPOX-7 Oxidizer®)
- ▶ HUSKY 907 O/O Conc. Multi-Purpose Cleaner & Degreaser (with HyPOX-7 Oxidizer®)
- ▶ HUSKY 910 Industrial Strength Spray & Wipe Cleaner Degreaser
- ▶ HUSKY 911 Non-Chlorinated Industrial Solvent

OTHER LIQUID/AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Specialty Products
- ▶ Carpet Care
- ▶ Odor Control
- ▶ Skin Care
- ▶ Health Care
- ▶ Floor Care

901 SOLVENT BASED INDUSTRIAL CLEANER/DEGREASER

DIRECTIONS

PRODUCT DATA



1. Always dilute product properly and utilize proper protective equipment. Depending on soil buildup, dilute 1:100 (1.5 oz. per gallon) for light soil, 1:43 (3 oz. per gallon) for regular soil, 1:20 (5 oz. per gallon) for heavy soil buildup.




2. For use with auto scrubbing equipment, dilute product 1:43 (3 oz. per gallon) in the solution tank. Add 1 oz. per gallon of defoamer to the recovery tank. Rinse equipment after use.



3. For use with pressure washer equipment, dilute 1:43 (3 oz. per gallon) for regular soil and 1:20 (5 oz. per gallon) for heavy soil.

USDA Authorized
A4 and A8 Rating
Class I & II Ozone Depleting Chemical (ODC)
Phosphate-Free
Flash Rust Inhibitors
Chlorinated Solvents
Petroleum Distillates
DOT Regulated
Superior Cleaning

YES	NO
X	
	X
X	
X	
	X
	X
X	
X	



SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#'s	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
*2-Butoxyethanol	111-76-2	25 ppm	25 ppm	N/A	5-10
Sodium Hydroxide	1310-73-2	2mg/M ³	2mg/M ³	N/A	1-5
Sodium Metasilicate	6834-92-0	N/A	N/A	N/A	1-5
Sodium Xylene Sulfonate	1300-72-7	N/A	N/A	N/A	1-5
Sodium Dodecylbenzene Sulfonate	25155-30-0	N/A	N/A	N/A	1-5

*This chemical is subject to the reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	≈212° F	Specific Gravity (H ₂ O=1)	1.080
Vapor Pressure (mm Hg.)	N/E	Percent Volatile By Weight (%)	>80%
pH (conc.)	13.5	Evaporation Rate (H ₂ O=1)	≈1
Solubility in Water	Complete		
Appearance and Odor	Red Liquid-Floral Fragrance		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >150°F (TCC) **Flammable Limits:** LEL: N/A UEL: N/A
Extinguishing Media: Water, CO₂, Foam or media suitable for surrounding fire
Special Fire Fighting Procedures: Standard fire fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: None Known

SECTION V - PHYSICAL HAZARDS

Stability Unstable **Conditions to Avoid:** None Known
 Stable
Incompatibility (Materials to Avoid): Do not mix with other chemicals.
Hazardous Decomposition Products or By-products: Thermal decomposition or burning may produce toxic vapors or gases.
Hazardous May Occur **Conditions to Avoid:** None Known
Polymerization Will Not Occur

SECTION VI - HEALTH HAZARDS

Route(s) of Entry: Inhalation? X Skin? X Ingestion? X
Health Hazards (1. Acute and 2. Chronic) 1. Acute: Harmful or fatal if swallowed. May cause permanent damage if not promptly treated. **2. Chronic:** None Known
Chemical Listed as Carcinogen or Potential Carcinogen:
National Toxicology Program: No
I.A.R.C. Monographs: No
OSHA: No

Signs and Symptoms of Exposure: Irritation or burning sensation.
Medical Conditions Generally Aggravated by Exposure: May aggravate skin disorders or respiratory ailments.
Emergency and First Aid Procedures: **Eye Contact:** Flush immediately with water for 15 minutes. Get medical attention. **Skin Contact:** Flush with water for 15 minutes. Remove and wash contaminated clothing. **Ingestion:** Rinse mouth with water. Then drink 1-2 glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention. **Inhalation:** Move to fresh air. Get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.
Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.
Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.
Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Not expected to be necessary under normal conditions of use. Where exposure cannot be adequately controlled by general or local ventilation, use appropriate respiratory protection to prevent over exposure. An approved dust/mist respirator would be recommended. **Ventilation: Local Exhaust:** As necessary
Mechanical (General): Adequate **Special:** N/A **Other:** N/A **Protection Gloves:** Water Impervious (Latex, Neoprene) **Eye Protection:** Chemical Resistant Goggles or Face Shield
Other Protective Clothing Or Equipment: Eye Wash Station Recommended
Work/Hygiene Practices: Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply. Wash thoroughly after handling.

N/A (Not applicable / Not available)
N/E (Not Established)