

FAST ACTING... a highly efficient, heavy duty degreaser designed to easily and economically clean a large variety of industrial and commercial areas. A remarkably fast-acting, deep penetrating cleaner ... greatly reduces labor costs. Formulated to handle the very toughest jobs.

SUPERB VERSATILITY... depending on the water dilution, this product performs light duty, general cleaning jobs ... or attacks the very toughest ones such as heavy grease and carbon deposits, soap scum, and rubber transfers. Because of its low foaming and powerful cleaning action, can be used successfully in hot tanks, spray equipment, dip tanks, steam cleaners, and automatic scrubbers.

GENERAL DIRECTIONS FOR USE

1. Dilution chart is shown indicating the various water ratios to be used depending on the surfaces to be cleaned. It is recommended that the user experiment with various water dilutions in order to determine the most economical ratio before establishing a cleaning procedure.
2. After surface has been cleaned, rinse thoroughly.

SAFETY DATA

DANGER: Harmful or fatal if swallowed. May cause skin or eye damage if not promptly treated. Wear eye protection and resistant (rubber) gloves when handling. Avoid breathing vapor, spray or mist. May cause respiratory tract irritation, if inhaled. Use with adequate ventilation. If necessary to prevent exposure, (e.g. when sprayed) wear approved respiratory protection.
CONTAINS: Water CAS# 7732-18-5, Sodium hydroxide CAS# 1310-73-2, 2-Butoxyethanol CAS# 111-76-2, Sodium Metasilicate CAS# 6834-92-0, Alcohol Ethoxylate CAS# 68131-39-5.

Manufactured By:
CANBERRA CORPORATION
 3610 Holland-Sylvania Rd.
 Toledo, Ohio 43615

THE NEXT LEVEL
 in CLEANING & MAINTENANCE

Regular Uses:	Recommended Water Dilutions:	
Floors, Walls, General Maintenance:		
light soil.....	1:30	(4 oz./gal.)
medium soil.....	1:10	(12 oz./gal.)
heavy soil.....	1:5	(21 oz./gal.)
Air Filters.....	1:2	(43 oz./gal.)
Engines, Machines, Equip. (43 oz./gal.)		12
Hoods, Flues.....	1:2	(43 oz./gal.)
Conveyors.....	1:4	(26 oz./gal.)
Concrete, Brick, Stucco....	1:2	(43 oz./gal.)
Light Fixtures, Appliances	1:10	(12 oz./gal.)
Ducts, Grills.....	1:5	(21 oz./gal.)
Kitchen Walls, Terrazzo, Marble, Ceramic Tile, Asphalt Tile.	1:8	(14 oz./gal.)

HUSKY 900 INDUSTRIAL STRENGTH DEGREASER

Corrosive material. Combustible liquid. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep away from sources of ignition - no smoking. If in contact with eyes, immediately flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately.

READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.

Matière corrosive. Liquide combustible. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Conserver à l'écart de toutes sources d'ignition - ne pas fumer. En cas de contact avec les yeux, laver immédiatement à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT.**

CANBERRA CORPORATION

Made in U.S.A.

For Industrial and Institutional Use Only
 Keep From Freezing

050510



This container is coded for Recycling



College of Knowledge

IEHA Certified Training & Education Available on CD ROM



900

INDUSTRIAL STRENGTH DEGREASER

A Fast-Acting, High Performance Degreaser For The Toughest Jobs

KEEP OUT OF REACH OF CHILDREN

DANGER:

See back panel for additional precautionary information.
 Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

