

**INSTANT OIL EMULSIFICATION...** a heavy duty, non-butyl, industrial detergent to be used in daily maintenance tasks where grease, lubricants, and cutting oils are used routinely on equipment. Holds oil and grease in an emulsified state for unusually extended periods of time.

**VERSATILITY PLUS SAFETY...** product's top notch grease/oil emulsification and retention property enables it to be used on everything from light cleaning to heavy duty degreasing.

**PLEASANT FRAGRANCE... BUT POWERFUL...** provides superb oil and grease removal,

yet leaves the area with a pleasant fragrance. Actually destroys disagreeable odors. Excellent for use in areas where products of this type are needed with only brief intervals between use.

**GENERAL DIRECTIONS FOR USE**

1. Dilution chart is shown indicating the various water ratios to be used depending on the surfaces to be cleaned. It is recommended that the user experiment with various water dilutions in order to determine the most economical ratio before establishing a cleaning procedure.
2. After surface has been cleaned, rinse thoroughly.

**SAFETY DATA CAUTION:** May cause eye or skin irritation. May cause respiratory tract irritation. Avoid breathing vapors, spray or mist. Use with adequate ventilation. Wear safety goggles and resistant gloves. May be harmful if ingested.

**CONTAINS:** Water CAS# 7732-18-5, Sodium Hydroxide CAS# 1310-73-2, Sodium Carbonate CAS# 497-19-8, Sodium Metasilicate CAS# 6834-92-0, Alcohol ethoxylate CAS# 68439-46-3.

**THE NEXT LEVEL**  
in **CLEANING & MAINTENANCE**

Regular Uses:	Recommended Water Dilutions:	
General Maintenance:		
heavy soil .....	1:2	(43 oz./gal.)
medium soil .....	1:10	(12 oz./gal.)
light soil .....	1:30	(4 oz./gal.)
or .....	1:50	(2.5 oz./gal.)
Appliances, Lawn Mowers, Electric Motors .....	1:15	(8 oz./gal.)
Conveyors, Lift Trucks, Diesel Units, Metal Working & Stamping Machines, Printing Presses .....	1:10	(12 oz./gal.)
White Side Walls .....	1:10	(12 oz./gal.)
Concrete, Swimming Pools .....	1:15	(8 oz./gal.)
Vending Machines .....	1:15	(8 oz./gal.)
Oil Spills or Oil on Floors from Tool and Die Equipment .....	1:10	(12 oz./gal.)
Air Conditioning and Heating Filters .....	1:15	(8 oz./gal.)


**HUSKY 902 NON-BUTYL INDUSTRIAL DETERGENT COMPLEX**

Corrosive material. Combustible liquid. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep away from sources of ignition - no smoking. If in contact with eyes, immediately flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Matière corrosive. Liquide combustible. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Conserver à l'écart de toutes sources d'ignition - ne pas fumer. En cas de contact avec les yeux, laver immédiatement à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT.**

**CANBERRA CORPORATION**

Made in U.S.A. 050510  
For Industrial and Institutional Use Only  
Keep From Freezing

 This container is coded for Recycling

 College of Knowledge  
IEHA Certified Training & Education Available on CD ROM



Manufactured By:  
**CANBERRA CORPORATION**  
3610 Holland-Sylvania Rd.  
Toledo, Ohio 43615



**902**

**NON-BUTYL INDUSTRIAL DETERGENT COMPLEX**

A Fast-Acting, Heavy Duty Industrial Detergent

KEEP OUT OF REACH OF CHILDREN

**CAUTION:**  
See back panel for additional precautionary information.  
Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

