

FAST ACTING... a highly efficient, heavy duty foaming degreaser designed to easily and economically clean a large variety of surfaces found in all areas of food service/processing plants. A remarkably fast-acting, deep penetrating foaming cleaner... that reduces labor costs. Formulated to handle the very toughest jobs.

SUPERB VERSATILITY... depending on the water dilution, this product performs light duty general cleaning jobs... or attacks the very toughest such as heavy grease and carbon deposits, animal fats, oils and food residues.

Because of its high foaming and powerful cleaning action, this product can be used successfully in foaming equipment, dip tanks, steam cleaners, and auto scrubbers for horizontal as well as vertical applications.

GENERAL DIRECTIONS FOR USE

- Dilution chart is shown indicating the various water ratios to be used depending on the surfaces to be cleaned. It is recommended that the user experiment with various water dilutions in order to determine the most economical ratio before establishing a cleaning procedure.
- After surface has been cleaned, rinse thoroughly.

SAFETY DATA DANGER: Harmful or fatal if swallowed. May cause skin or eye damage if not promptly treated. Wear eye protection and resistant (rubber) gloves when handling. Avoid breathing vapor, spray or mist. May cause respiratory tract irritation, if inhaled. Use with adequate ventilation. If necessary to prevent exposure, (e.g. when sprayed) wear approved respiratory protection.

CONTAINS: Water CAS# 7732-18-5, Sodium hydroxide CAS# 1310-73-2, 2-Butoxyethanol CAS# 111-76-2, Surfactant CAS# 9016-45-9.

Manufactured By:
CANBERRA CORPORATION
 3610 Holland-Sylvania Rd.
 Toledo, Ohio 43615

**THE
 NEXT LEVEL**
 in CLEANING & MAINTENANCE


Regular Uses:	Recommended Water Dilutions:	
Floors, Walls, General Maintenance:		
light soil	1:50	(2 1/2 oz./gal.)
medium soil	1:20	(6 oz./gal.)
heavy soil	1:10	(12 oz./gal.)
Air Filters	1:5	(21 oz./gal.)
Engines, Machines, Equipment	1:5	(21 oz./gal.)
Hoods, Flues	1:5	(21 oz./gal.)
Conveyors	1:10	(12 oz./gal.)
Concrete, Brick, Stucco ...	1:5	(21 oz./gal.)
Light Fixtures, Appliances	1:20	(6 oz./gal.)
Ducts, Grills	1:5	(21 oz./gal.)
Kitchen Walls, Terrazzo, Marble, Ceramic Tile, Asphalt Tile	1:20	(6 oz./gal.)

HUSKY 903 FOOD SERVICE FOAMING DEGREASER

Corrosive material. Combustible liquid. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep away from sources of ignition - no smoking. If in contact with eyes, immediately flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Matière corrosive. Liquide combustible. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Conserver à l'écart de toutes sources d'ignition - ne pas fumer. En cas de contact avec les yeux, laver immédiatement à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement. **LIRE LA FICHE SIGNALÉTIQUE AVANT D'UTILISER CE PRODUIT. CANBERRA CORPORATION**

Made in U.S.A.
For Industrial and Institutional Use Only
Keep From Freezing

 This container is coded for Recycling

 College of Knowledge
 IEHA Certified Training &
 Education Available on CD ROM



903

**FOOD SERVICE
 FOAMING DEGREASER**

**A Heavy Duty Foaming Degreaser
 Concentrate For The Removal of
 Proteins, Oils and Fats**

DANGER:
 Keep Out Of Reach Of Children

See back panel for additional precautionary information.
 Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters

